

DHI-ARC9016C-(G)

MBus Alarm Controller



Features

- 16 on-board zones, expansion to 256 zones(ARM801/ARM802/ARM808/ARM808-S/ARM911)
- Up to 16 partitions
- 8 alarm out, expansion to 64(ARM708/ARM716/ARM911)
- 8 alarm keypad (ARK10C)
- 2 pairs of MBus line, up to 2.4km for each bus line
- TCP/IP, 2G(-G only), PSTN

Technical Specification

Wired Zones	16 on-board zones, expansion to 256 zones (ARM801/ARM802/ARM808/ARM808-S/ARM911)
Alarm Output	8 relay output (30VDC 1A), expansion to 64 (ARM708/ARM716/ARM911)
Network	1-ch 10M/100M RJ45 Ethernet port, -G (GSM network)
Protocol	TCP/IP
Log	1024
Independent security service center	2 groups phone call security center
Siren	Support
PSTN Detect	Support
Anti-cut, Anti-circuit	Support
SMS	-G Support
Remote Upgrade	Support
Tamper Alarm	Vandal proof
Alternate Power	12V/7Ah Lead-acid battery
Power	DC14.5V, Max 35W
Working Environment	-10°C~+55°C

Dimensions	275*275*77mm
Weight	<3kg
Installation	Wall mounting

DHI-ARC9016C-(G)

Ordering Information

Type	Part Number	Description
Controller	DHI-ARC9016C	MBus Alarm Controller
Controller	DHI-ARC9016C-G	MBus Alarm Controller with 2G SIM card slot
Keypad	DHI-ARK10C	Alarm keypad, Max. 8pcs

Dimensions

