

WiFi Outdoor 4G Router

Pulsar Uniti LTE Outdoor

SERIES

Outdoor

Models

Pulsar Uniti LTE Outdoor



MAIN FEATURES

- 1 Omnidirectional high-gain antenna, 360° reception of 4G signal, stable Internet access
- 2 The three networks are universal
- 3 Hardware watchdog function, free of manual maintenance, 4G drop detection
- 4 It supports 24V POE and DC12V power supply modes
- 5 Remote management
- 6 Watchdog protection
- 7 All network connectivity
- 8 SIM card slot



www.pulsar.az

Pulsar Uniti LTE Outdoor

Model	Pulsar Uniti LTE Outdoor
Hardware Specifications	
Flash	16MB
DDR	128MB
Frequency	802.11/N/B/ Frequency:2.4GHz+5GHz
Data Rate	300Mbps
4G Antenna	Gain: 3dbi
WIFI antenna	Gain: 2dbi
Ports	1 * 10/100M RJ45 WAN port, support PoE 1 * 10/100M RJ45 LAN port 1 * 4G SIM card slot
Water-Proof Level	IP65
DC	12V 1A
POE	24V 0.5A
Reset	reset×1 (Press 10 seconds to revert to factory settings)
LED Indicator	POWER ,WAN ,LAN,WLAN, Signal strength * 4
Power consumption	< 11W
Performance	
LTE Module Model	Quectel EC25-AU, LTE-CAT4
Band Support	GSM: B2/3/5/8;
	WCDMA: B1/2/5/8;
	LTE FDD: B1/2/3/4/5/7/8/28; LTE TDD: B40
LTE Data Rate	LTE-FDD: max 150(DL)/Max 50(UL)
	LTE-TDD: max 130(DL)/Max 35(UL)
Configuration	
Wi-Fi	Support Auto Channal, Guest SSID, SSID hide Wireless MAC filter, white and black list
Net	PPPoE, Automatic IP, Static IP, L2TP, PPTP, 4G
	Support automatically switch between WAN/ISP and 4G Support VPN server and VPN client: PPTP, L2TP and OpenVPN Support AP+Client
Firewall	Support NAT, URL Filter, MAC Filter and Network Service Filter
	Support DoS attack protection, SYN flood attack WAN PING,SSH, HTTP Access
Other functions	NTP and account setup;
	Port forwarding
	Virtual Server
	Watchdog
	DMZ
Size	DDNS
L*W*H	196mm*86mm*40mm
Weight	0.4kg
Working Environment	
Working temperature	-30°C~55°C
Limited working temperature	-40°C~70°C
Storage Temperature	-40°C~70°C
Storage Humidity	5%~95% No Condensation