

# **DHI-HY-C102-4**

# Conventional Fire Alarm Control Panel



- 90VAC to 270VAC main power supply ensures the stable operation
- 4 dry contacts make connection flexible
- Ethernet interfaces enables communication with IoT platform
- RS-485 interface contributes to convenient integration
- Record and export capacity of historical events for each of fire, fault and operation

## **System Overview**

DHI-HY-C102-4 Conventional Fire Alarm Control Panel is designed and manufactured in compliance with EN54 Parts 2 & 4 requirements. As the core of conventional fire alarm system, it cooperates with smoke detectors, heat detectors, sounder strobes, and manual call points to construct a fire alarm control system. With Ethernet, RS-485, and other IoT interfaces, it can integrate with other panels and connect to platforms.

## **Functions**

#### **Alarm Function**

After receiving alarm signals from detectors or manual call points, it will promptly send visual and audible alarm signals, output fire alarm, start remote fire bell and sounder strobe.

#### **Platform Access**

With built-in Ethernet interface, it can connect with platform to enable IoT communication.

#### **System Linkage**

Built-in RS-485 interface supports panel linkage.

#### **Data Output**


The system saves fire alarm records and simulation records, outputs and analyzes the data.

### Scene


It is suitable for residential and industrial buildings such as hotels, shopping malls, hospitals, office buildings, schools, banks, libraries, factories, and warehouses.


Technical Specification		
Number of Zones	4	
Zone Capacity	32 detectors per zone	
Main Power	AC90-240V/50Hz, 60Hz	
Backup Power	2 lead-acid batteries (12V/5Ah each)	
Output Current	2A	
Sounder Output	Fault: 50dB Alarm: 60dB	
Fire Bell Output	DC 28V/500mA	
Dimensions	310.0 mm×73.0 mm×227.0 mm (12.20" × 2.87" × 8.94")	
Weight	3.5 kg 5 kg (with 2 batteries)	
Operating Temperature	-10°C to +50°C (+14°F to +122°F)	
Operating Humidity	≤ 95% RH (no condensation)	
Protection Grade	IP30	
Installation	Wall mount	
Compliance Standard	EN54-2,EN54-4	

## Installation



# Dimensions (mm/inch)





Ordering Information			
Туре	Part Number	Description	
Conventional Fire Alarm Control Panel	DHI-HY-C102-4	Conventional Fire Alarm Control Panel	