

Unmanaged Gigabit Poe Switch

Pulsar Uniti switch 24GP-260

SERIES

Unmanaged Switch

Models

Pulsar Uniti switch 24GP-260

**MAIN FEATURES**

- 1 The POE detection chip adopts the 802.3af/at standard protocol
- 2 The design life is 3 years
- 3 The high-frequency and low-resistance capacitors make the equipment performance more st
- 4 A single port supports the AT protocol and supports up to 30W
- 5 Port are automatically flipped
- 6 Plug-and-play simple networking
- 7 The metal body dissipates heat efficiently stable operation
- 8 Efficient data transfer
- 9 AC and cold start function
- 10 Gigabit up-link port and Gigabit PoE ports
- 11 The product has undergone rigorous support code testing
- 12 Designed with desktop metal case
- 13 Easy to make the transition to Gigabit Ethernet.
- 14 Port VLAN division is supported, that is, port isolation.
- 15 Gigabit SFP fiber injector



www.pulsar.az

Pulsar Uniti switch 24GP-260

Model	Uniti switch 24GP-260
Hardware Specifications	
Network standard	IEEE802.3 10BASE-T Ethernet IEEE802.3u 100BASE-TX faster Ethernet IEEE802.3ab 1000BASE-T gigabit Ethernet ANSI/IEEE 802.3 NWay Auto-Negotiation IEEE802.3 af IEEE802.3at
Ports	24 * 10/100/1000M auto Negotiation /auto MDI/MDIX PoE Ports 2 * 10/100/1000M auto Negotiation /auto MDI/MDIX up-link Port 2 * 1000Base-X SFP Fiber Ports
Cable requirement	10BASE-T: UTP 3, 4, 5 cable (≤100 meters) 100BASE-TX: UTP 5 cable (≤100 meters) 1000BASE-TX: UTP 5 cable (≤100 meters)
Property	Connector: RJ-45, SFP. Support 10M/100M/1000 Mbit/s data rate Support half duplex, full duplex, self negotiation mode Support MDI/MDI-X adaptive Support VLAN port isolation
IEEE802.3 af	Support/15.4W
IEEE802.3at	Support/30W
LED Indicator	Per Port:1000 LINK/Act ; 10/100M Link/Act Per Device: POWER
Power Supply	AC 100 V~240 V 50/60 Hz
Power over Ethernet (PoE) Specifications	
POE	260W up to 30W for PoE port
PoE Standard	IEEE 802.3, 802.3u, 802.3x, 802.3af,802.3at
Overload Protection	250W
Switch Performance	
Advanced Functions	Comply with IEEE 802.3at/af PDs Port Priority Function Support storage forwarding MAC Address Auto-Learning and Auto-Aging. IEEE802.3X Flow Control for Full-Duplex Mode and Backpressure for Half-Duplex Mode
Backplane Bandwidth	56Gbps
MAC Address Table	Support MAC address automatic learning, automatic aging MAC Address Table: 8K
Forwarding Rate	10BASE-T:14800pps/port 100BASE-TX:148000pps/port 1000BASE-TX:1480000pps/port
Size	
L*W*H	440mm*221,5mm*45mm
Weight	4 kg
Working Environment	
Working Temperature:	0°C~40°C
Storage Temperature	-40°C~70°C
Working Humidity	10%~90% No Condensation
Storage Humidity	5%~90% No Condensation