

# DS-7116NI-Q1/M

## Hikvision NVR

|               |                |
|---------------|----------------|
| Model         | DS-7116NI-Q1/M |
| Brend         | Hikvision      |
| Növ           | NVR            |
| Kanal sayı    | 16 kanal       |
| Meqapixeł     | 4 MP           |
| Max HDD sayı  | 1 HDD          |
| Max HDD həcmi | 6 TB           |



### Specification

Video and audio

|                  |                                                                                      |
|------------------|--------------------------------------------------------------------------------------|
| IP video input   | 16 channels<br>Resolution up to 4 MP                                                 |
| Input Bandwidth  | 40 Mbit/s                                                                            |
| Output Bandwidth | 60 Mbit/s                                                                            |
| HDMI output      | 1 channel, 1920 × 1080p/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz |
| VGA output       | 1 channel, 1920 × 1080p/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz |
| Video output     | Simultaneous HDMI/VGA output                                                         |

Decoding

|                       |                                                           |
|-----------------------|-----------------------------------------------------------|
| Decoding Format       | H.265+ / H.265 / H.264+ / H.264                           |
| Recording permission  | 4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF     |
| Synchronized playback | 16 channels                                               |
| Playback options      | 16 channels, @ 1080p (25 fps), 2 channels @ 4 MP (25 fps) |
| Stream type           | Video, video and audio                                    |

Net

|                   |                                                              |
|-------------------|--------------------------------------------------------------|
| Remote connection | 16                                                           |
| Network protocol  | TCP/IP, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, UPnP™ |
| Network interface | 1, RJ45 auto 10/100M Ethernet                                |

Auxiliary Interfaces

|                      |                       |
|----------------------|-----------------------|
| SATA                 | 1 SATA interface      |
| Capacity             | Up to 6 TB each drive |
| Alarm inputs/outputs | -                     |
| USB                  | Rear: 2 × USB 2.0     |

Basics

|                                 |                                       |
|---------------------------------|---------------------------------------|
| Nutrition                       | DC 12 V, 1.5 A                        |
| Power consumption (without HDD) | ≤ 10 W                                |
| Working temperature             | -10 to +55 °C                         |
| Operating humidity              | From 10 to 90%                        |
| Dimensions                      | 265 × 225 × 48 mm (10.4 × 8.9 × 1.9") |
| Weight (without storage)        | ≤ 1 kg                                |

Certificates

|      |                                       |
|------|---------------------------------------|
| FCC  | Part 15 Subpart B, ANSI C63.4-2014    |
| C.E. | EN50130-4, EN 61000-3-2, EN 61000-3-3 |