

## ABOUT SRNE

- $\square$  SRNE 15 years in PV industry, committed to independent R&D and production.
- ☐ Holds over 200 patents in energy storage, with unique industryleading technologies.
- ☐ Chooses top-quality international components to deliver highvalue products to customers.
- ☐ Upholds values of customer priority, proactivity, responsibility, and innovative breakthroughs.



MODEL		HF1210S60-108			HF1215S60-108	
INVERTER OUTPUT				<b>'</b>		
Rated Output Power		1,000W			1,500W	
Max.Peak Power		2,000VA			3,000VA	
Rated Output Voltage		230Vac (Single-Phase)				
Load Motor Capacity		1HP				
Rated Frequency		50/60Hz				
Waveform		Pure sine wave				
Switch Time		10ms (typical)				
BATTERY						
Battery Type		Lead-Acid / Li-ion / User-Define				
Rated Battery Voltage		12V				
Battery Volatge Range		10.5~15.5Vdc				
Max. Solar Charging Current		60A				
Max. Grid/Generator Charging Current		60A				
Max. Hybrid Charging Current		120A				
SOLAR INPUT						
No. Of MPPT		1				
Max.PV Array Power		1,000W				
Max. Input Current		28.5A				
Max. Open Circuit Voltage		108Vdc				
MPPT Voltage Range		15~90Vdc				
GRID/GENERATOR INPUT						
Input Voltage Range		170~280Vac				
Input Frequency Range		50/60Hz				
Bypass Overload Current			6.5A		9.7A	
EFFICIENCY						
MPPT Tracking Efficiency		99.9%				
Max. Efficiency		92%				
GENERAL DATA						
Dimension	357.5*23	35*103mm	Moisture		0~100%	
Weight	5.5kg		Cooling Method	b	Fan Cooling	
Protection Degree	IP20 Only Indoor		Warranty		2 years	
Temperature	-10°C~55°C		Communication		RS485/CAN/USB/Dry Contac	
External Module (Optional)	Wi-Fi/GPRS		Topology		Transformerless	
Certificate	RoHs/IEC	Hs/IEC 62109/EN61000/C2				

## PROTECTION

Equipped with PV current limit and power limit protection, PV night anti-reverse charging protection, utility input over-voltage protection, utility input under-voltage protection, battery over-voltage protection, battery under-voltage protection, load output short-circuit protection.