

Elevator wireless bridge

Pulsar Uniti X5 Elevator

SERIES

Elevator

Models

Pulsar Uniti X5 Elevator



MAIN FEATURES

- 1 Designed for elevator solutions
- 2 Supports Repeater mode and AP mode
- 3 Built-in 6dBi directional antenna, dedicated to elevators.
- 4 Supports intelligent channel analysis, automatic optimal channel selection
- 5 Remote management
- 6 Support one-click pairing.
- 7 APP management
- 8 AC management



Pulsar Uniti X5 Elevator

Model	Pulsar Uniti X5 Elevator				
Hardware Specifications					
Flash	8MB				
DDR	64MB				
Frequency	802.11 b / g / n				
Data Rate	300Mbps				
WIFI antenna	2.4G directional panel antenna, gain : 6dBi				
Ports	1*10/100M WAN, support 24V passive POE 1*10/100M LAN				
Water-Proof Level	IP65				
DC	12V 1A				
POE	PoE 24V				
Reset	Long press for 10 seconds to restore the factory default configuration, and short press for 1 second to initiate pairing				
Switch button	Choose AP/ Repeater working mode				
Ppm	±20ppm				
2.4G TX Power	802.11b	11M	19±2dBm	1M	20±2dBm
	802.11g	54M	17±2dBm	6M	19±2dBm
	802.11n HT20	MCS7	16±2dBm	MCS0	18±2dBm
	802.11n HT40	MCS7	16±2dBm	MCS0	18±2dBm
2.4G Receiving Sensitivity	802.11b	11M	-85dBm	1M	-94dBm
	802.11g	54M	-73dBm	6M	-90dBm
	802.11n HT20	MCS7	-71dBm	MCS0	-89dBm
	802.11n HT40	MCS7	-68dBm	MCS0	-86dBm
2.4G EVM	802.11b: ≤-10 dB ; 802.11g: ≤-25 dB ; 802.11n: ≤-28dB				
LED Indicator	SYS, WAN, LAN, WIFI, signal*4				
Power consumption	<3W				
Electrical Surge	Common Mode: 2K, Differential Mode: 1K				
ESD	Air:±8K, Touch:±6K				
Size					
Dimension	168mm*86mm*39mm				
Weight	0.5kg				
Working Environment					
Working temperature	-30°C~55°C				
Limited working temperature	-40°C~70°C				
Storage Temperature	-40°C~70°C				
Storage Humidity	5%~95% No Condensation				