

DS-TMG420**Barrier gates with straight boom pole**

DS-TMG420-X series barrier gate is applicable to entrance and exit management. It is widely used in road toll stations, parking lots, communities, enterprise entrances and exits, etc. to manage the entering and exiting of vehicles and record vehicle passing times. It can be controlled automatically via parking lot management system, or via handle, remote controller, button, etc.

- Adopts integrated machine core. Parallel gear decelerates linkage arm transmission to ensure stability and efficiency.
- Supports convenient side installation with compact structure.
- Adopts quenching process for carbon steel gear to realize wear-resistant and impact-resistant functions and extend product life.
- Adopts small DC brushless motor with low noise to increase output torque and realize precise intelligent control.
- Supports rebound for obstacle and opening priority.
- Adopts DC variable frequency control to enable smooth operation with fast boom pole opening and slow boom pole closing.
- Supports event log to enable convenient monitoring.
- Supports multiple anti-fall modes such as IR, vehicle detectors, and radars.
- Supports fault code detection on the nixie tube, log record, and abundant status indicating. Based on the fault code displayed on the nixie tube, you can realize quickly problems locating and maintenance.
- Supports manually opening boom pole. You can turn hand wheel to keep barrier gate opening during power cutoff.
- Delayed boom pole closing (10 s delay time by default). Supports 99 shifts (initial status 2 s, 2 s gap between each shift).
- Supports auto boom pole opening during power cutoff. The barrier gate can open automatically to allow fire trucks in (optional components required).

▪ Specification


Barrier Housing	
Barrier Housing Material	SGCC
Barrier Housing Thickness	1.5 mm
Barrier Housing Door Thickness	1.2 mm
Barrier Housing Color	Iron gray
Barrier Housing Door Color	Orange red
Boom Pole Installation Height	885 mm
Body Indicators	DS-TMG420, DS-TMG420-L, DS-TMG420-R: no body indicator DS-TMG420/B, DS-TMG420-L/B, DS-TMG420-R/B, DS-TMG420/A/B, DS-TMG420-L/A/B, DS-TMG420-R/A/B: with body indicator. Green: arrow indicator. Red: prohibition indicator
Barrier Gate General	
Rising Speed	3m octagonal and 3m anti-collusion round: 2s, 4m octagonal and 4m anti-collusion round: 3s, 6m octagonal: 5s
Falling Speed	3m octagonal and 3m anti-collusion round: 2s, 4m octagonal and 4m anti-collusion round: 3s, 6m octagonal: 5s
Boom Pole Direction	DS-TMG420, DS-TMG420/B, DS-TMG420/A/B: right by default, direction switchable DS-TMG420-L/B, DS-TMG420-L/A/B: Left DS-TMG420-R/B, DS-TMG420-R/A/B: Right
Motor Type	DC brushless motor
Matched Boom Pole Type	Cylinder boom pole: 1 to 4 m, anti-collision Octagonal boom pole: 1 to 6 m Octagonal telescopic boom pole: 4 to 6 m Boom pole $\geq$ 5 m: with spindle rod
Boom Pole Falling Delay	10 s by default (configurable), min. 2 s (every 2 s followed a gap)
Number of Cycles	5,000,000
Consumption	DS-TMG420, DS-TMG420-L, DS-TMG420-R: Max. 125 W DS-TMG420/B, DS-TMG420-L/B, DS-TMG420-R/B: Max. 139 W DS-TMG420/A/B, DS-TMG420-L/A/B, DS-TMG420-R/A/B: Max. 155 W
Temperature and Humidity	Temperature: -30 °C to 60 °C (-22 °F to 140 °F), Humidity: $\leq$ 90%
Working Voltage	100-120VAC / 200-240VAC (default 220-240V , switchable)
Rising Boom Pole for Poweroff	Optional, not supported by default
Barrier Gate	
Duty Cycle	100%
Interface	
RS-485	1 group
Rising to Limit	1 group
Falling to Limit	1 group
Open	1 group
Close	1 group
Stop	1 group
IR/Vehicle Detector/Radar	1 group
Traffic Signal Light	1 group, external power supply required, max. 220 VAC supported
Boom Pole	
Boom Pole Color	White background with red bar



Boom Pole Weight	2 m octagonal boom pole: 2.5 ± 0.3 kg (5.51 ± 0.66 lb.) 3 m octagonal boom pole: 2.8 ± 0.3 kg (6.17 ± 0.66 lb.) 4 m octagonal boom pole: 3.45 ± 0.3 kg (7.60 ± 0.66 lb.) 5 m octagonal boom pole: 5.9 ± 0.3 kg (13.00 ± 0.66 lb.) 6 m octagonal boom pole: 6.8 ± 0.3 kg (15.21 ± 0.66 lb.) 3 m boom pole with LED strip light: 3.4 ± 0.3 kg (7.50 ± 0.66 lb.) 4 m boom pole with LED strip light: 4.4 ± 0.3 kg (9.70 ± 0.66 lb.) 4 m octagonal telescopic boom pole: 4.42 ± 0.3 kg (9.74 ± 0.66 lb.) 5 m octagonal telescopic boom pole: 4.85 ± 0.3 kg (10.69 ± 0.66 lb.) 6 m octagonal telescopic boom pole: 5.65 ± 0.3 kg (12.46 ± 0.66 lb.) 2 m anti-collision round boom pole: 2.5 ± 0.3 kg (5.51 ± 0.66 lb.) 3 m anti-collision round boom pole: 3.5 ± 0.3 kg (7.71 ± 0.66 lb.) 4 m anti-collision round boom pole: 4.5 ± 0.3 kg (9.92 ± 0.66 lb.)
Boom Pole Dimensions (with Package)	2 m octagonal boom pole: $115 \times 60 \times 2020$ mm ($4.53 \times 2.36 \times 79.53$ inch) 3 m octagonal boom pole: $115 \times 60 \times 3020$ mm ($4.53 \times 2.36 \times 118.90$ inch) 4 m octagonal boom pole: $115 \times 60 \times 4020$ mm ($4.53 \times 2.36 \times 158.27$ inch) 5 m octagonal boom pole: $140 \times 65 \times 5030$ mm ($5.51 \times 2.56 \times 198.03$ inch) 6 m octagonal boom pole: $140 \times 65 \times 6030$ mm ($5.51 \times 2.56 \times 237.40$ inch) 3 m boom pole with LED strip light: $100 \times 60 \times 3035$ mm ($3.94 \times 2.36 \times 120.07$ inch) 4 m boom pole with LED strip light: $100 \times 60 \times 4035$ mm ($3.94 \times 2.36 \times 159.45$ inch) 4 m octagonal telescopic boom pole: $120 \times 51 \times 3100$ mm ($4.72 \times 2.01 \times 122.05$ inch) 5 m octagonal telescopic boom pole: $120 \times 51 \times 3500$ mm ($4.72 \times 2.01 \times 137.80$ inch) 6 m octagonal telescopic boom pole: $120 \times 51 \times 4005$ mm ($4.72 \times 2.01 \times 157.68$ inch) 2 m anti-collision round boom pole: $90 \times 90 \times 2030$ mm ($3.54 \times 3.54 \times 79.92$ inch) 3 m anti-collision round boom pole: $90 \times 90 \times 3030$ mm ($3.54 \times 3.54 \times 119.29$ inch) 4 m anti-collision round boom pole: $90 \times 90 \times 4030$ mm ($3.54 \times 3.54 \times 158.66$ inch)
Boom Pole Weight (with Package)	2 m octagonal boom pole: 2.37 ± 0.3 kg (5.22 ± 0.66 lb.) 3 m octagonal boom pole: 3.11 ± 0.3 kg (6.86 ± 0.66 lb.) 4 m octagonal boom pole: 3.965 ± 0.3 kg (8.74 ± 0.66 lb.) 5 m octagonal boom pole: 7.01 ± 0.3 kg (15.45 ± 0.66 lb.) 6 m octagonal boom pole: 8.245 ± 0.3 kg (18.18 ± 0.66 lb.) 3 m boom pole with LED strip light: 4.0 ± 0.3 kg (8.82 ± 0.66 lb.) 4 m boom pole with LED strip light: 5.2 ± 0.3 kg (11.46 ± 0.66 lb.) 4 m octagonal telescopic boom pole: 5.11 ± 0.3 kg (11.27 ± 0.66 lb.) 5 m octagonal telescopic boom pole: 6.23 ± 0.3 kg (13.73 ± 0.66 lb.) 6 m octagonal telescopic boom pole: 7.25 ± 0.3 kg (15.98 ± 0.66 lb.) 2 m anti-collision round boom pole: 2.7 ± 0.3 kg (5.95 ± 0.66 lb.) 3 m anti-collision round boom pole: 4.3 ± 0.3 kg (9.48 ± 0.66 lb.) 4 m anti-collision round boom pole: 5.8 ± 0.3 kg (12.79 ± 0.66 lb.)


Color of Boom Pole with LED Strip Light	DS-TMG420, DS-TMG420-L, DS-TMG420-R, DS-TMG420/B, DS-TMG420-L/B, DS-TMG420-R/B: no boom pole with LED strip light DS-TMG420/A/B, DS-TMG420-L/A/B, DS-TMG420-R/A/B: with boom pole with LED strip light, green indicator for boom pole opening status Boom pole other status: red indicator Photometric parameters: Red: luminous flux 39.44 lm, light effect 17.86 lm/W Green: luminous flux 107.56 lm, light effect 45.65 lm/W Working life (lighting time): 5800 h
Boom Pole Dimensions	2 m octagonal boom pole: 98 × 45 × 2000 mm (3.86 × 1.77 × 78.74 inch) 3 m octagonal boom pole: 98 × 45 × 3000 mm (3.86 × 1.77 × 118.11 inch) 4 m octagonal boom pole: 98 × 45 × 4000 mm (3.86 × 1.77 × 157.48 inch) 5 m octagonal boom pole: 119 × 55 × 5000 mm (4.69 × 2.17 × 196.85 inch) 6 m octagonal boom pole: 119 × 55 × 6000 mm (4.69 × 2.17 × 236.22 inch) 3 m boom pole with LED strip light: 95 × 49 × 3013 mm (3.74 × 1.93 × 118.62 inch) 4 m boom pole with LED strip light: 95 × 49 × 4013 mm (3.74 × 1.93 × 157.99 inch) 4 m octagonal telescopic boom pole: 110 × 44 × 2970 mm (4.33 × 1.73 × 116.93 inch) 5 m octagonal telescopic boom pole: 110 × 44 × 3470 mm (4.33 × 1.73 × 136.61 inch) 6 m octagonal telescopic boom pole: 110 × 44 × 6000 mm (4.33 × 1.73 × 236.22 inch) 2 m anti-collision round boom pole: 80 × 80 × 2000 mm (3.15 × 3.15 × 78.74 inch) 3 m anti-collision round boom pole: 80 × 80 × 3000 mm (3.15 × 3.15 × 118.11 inch) 4 m anti-collision round boom pole: 80 × 80 × 4000 mm (3.15 × 3.15 × 157.48 inch)
Boom Pole Material	AL6061
Approval	
RF	CE-RED EN 300220-1 V3.1.1 EN 300220-2 V3.1.1 EN 301489-1 V2.2.3 EN 301489-3 V2.1.1 EN IEC 62311: 2020
EMC	CE-EMC : EN 55032: 2015/A11: 2020 + A1: 2020, EN IEC 61000-3-2: 2019/A1: 2021, EN 61000-3-3: 2013 + A1: 2019/A2: 2021, EN 50130-4: 2011 + A1: 2014
Security	CE-LVD: EN 62368-1: 2014/A11: 2017 CB: IEC 62368-1: 2014 IEC 62368-1: 2018
Environment	ROHS
Protection	IP54, IK09
Package	
Barrier Housing Dimensions (L × W × H)	1060 × 370 × 262 mm (41.73 × 14.57 × 10.31 inch)
Body Weight	43 ± 3 kg (94.8 ± 6.61 lb.)

Body Dimensions (with Package, Without Boom Pole) (L × W × H)	1266 × 504 × 626 mm (49.84 × 19.84 × 24.65 inch)
Body Weight (with Package, Without Boom Pole)	47 ± 3 kg (103.61 ± 6.61 lb.)

▪ Dimension











▪ Accessory

▪ Included

DS-TMG070/4B/4 2	DS-TMG001-5	DS-TMG012-5

▪ Optional

DS-TMG070/32/42	DS-TMG013-5	DS-TMG012-A1	DS-TVL221-1-6D	DS-TMG023
-----------------	-------------	--------------	----------------	-----------

				
DS-TMG022	DS-TMG000-2-R(hi gh speed)	DS-TMG000-2-R(lo w speed)	DS-TMG000-2-L(hig h speed)	DS-TMG000-2-L(lo w speed)
				
DS-TMG060-42	DS-TMG050	EEBracket-L800-100 0(barrier)	DS-TMG070/4B/42(24V)	TMG080-3
				
DS-TMG001-3				
				

See Far, Go Further



www.hikvision.com
support@hikvision.com

